


# DD-PAD - ABI Kit with Doppler



Primary Care



Podiatry



Wound Care



Single-Level

CLINIC PLACEMENT

EXAMS PERFORMED



American-Made Quality



Includes labor, parts, and accidental breakage

Newman Medical's DD-PAD is designed to quickly and easily produce the results you need for the diagnosis of lower extremity peripheral artery disease. All of our vascular ABI systems are Made in the USA and have an industry-leading 2 year warranty.

## DD-PAD Exams

- Single-Level

## DD-PAD Includes:

- Manual Aneroid
  - 1 x 10cm EZ-Clean Vasocuffs
  - 1 x 12cm EZ-Clean Vasocuffs
- Carry Bag
- Two-Year Warranty
  - Includes all parts, labor, and accidental breakage



## simpleABI Vascular Systems: Quality You Can Trust

### Made in the USA

- High-quality components, manufactured in Colorado.
- Durable design for busy clinical settings.
- 2-year warranty with complete coverage.



### Newman Medical: Your Partner in Vascular Care

- Leaders in ultrasound diagnostics since the 1970s.
- Committed to innovation and providing exceptional vascular products.
- Focused on service and long-term customer relationships.


### First-Class Support

- Experienced customer service team with extensive industry knowledge.
- Dedicated field representatives for personalized assistance.
- Comprehensive clinical support resources, both online and in-person.

## DD-PAD



## Exams Performed



Single-Level

## Ordering Information

### System

<b>SKU</b>	<b>DESCRIPTION</b>
DD-PAD	ABI Kit with 8MHz Doppler

### Accessories

<b>SKU</b>	<b>DESCRIPTION</b>
ACC-200	Set of 8 Cuff-Link Tubing
ACC-210	Set of 4 Cuff-Link Tubing
PUMP-100	Manual cuff inflator

### Replacement Cuffs

<b>SKU</b>	<b>DESCRIPTION</b>
CUFF-200	EZ Clean Vascular Cuff, 10cm (ankle, small arm)
CUFF-210	EZ Clean Vascular Cuff, 12cm (arm, ankle, calf)
CUFF-210L	EZ Clean Vascular Cuff, 12cm long (above knee)
CUFF-SET-242	EZ Clean Vascular Cuff Set - 2x10cm, 4x12cm, 2x12cm - 8/pk



## DD-PAD Technical Specifications

**Weight:** 3.6 kgs (8 pounds)

**Level of Protection against electrical shock:** Type B Applied Part, Class II Equipment

**Comply with the following Standards:** IEC60101-1, IEC60601-2, IEC60601-2-37

**Operating Temperature:** 10° ~ 40°C (50° ~ 104°F)

**Operating Humidity:** 30% ~ 75%

**Transport/Storage Temperature:** -20° ~ 50°C (-4° ~ 122°F)

**Transport/Storage Humidity:** 5% ~ 90%, non-condensing

**Battery Life:** 800, 1 minute exams

**GTIN:** 00852785008524

